

APC PROTECTNET TELECOM 2 LINE

Part Number: PTEL2



Input

Input Connections	--
-------------------	----

Surge Protection and Filtering

Peak Current Normal Mode	0.20 kAmps
Peak Current Common Mode	0.15 kAmps
NM Surge Response Time (ns)	1 ns
Dataline protection	RJ-45 Modem/Fax/DSL protection (four wire dual line)
Data Lines Protected (multi-line only)	3-6 RJ45
Let Through Voltage Rating	< 260

Physical

Net Weight	0.06 KG
Maximum Height	103.00 mm
Maximum Width	47.00 mm
Maximum depth	28.00 mm
Shipping Weight	0.14 KG

Shipping Height	104.00 mm
Shipping Width	90.00 mm
Shipping Depth	29.00 mm
Master Carton Units	144.00
Master Carton Weight	18.00 lbs.
SCC Codes	10731304000430
Color	Beige
Units per Pallet	750.00

Environmental

Operating Environment	-15 - 45 °C
Operating Relative Humidity	0 - 95%
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95%

Conformance

Regulatory Approvals	CSA,UL 497A,UL Listed
Standard Warranty	10 years repair or replace